



OUTPUT

Voltage	50Hz				60Hz			
	Prime		Standby		Prime		Standby	
	kVA	kW	kVA	kW	kVA	kW	kVA	kW
400/230	550	440	590	472				
480/277					551	440	600	480

Ambient reference conditions: Rating according to ISO 8528: +25°C, 100 ASL, 30% relative humidity.

Power lost according to DIN ISO 3046: Starting from 100m, 1% lost with each 100m increment. Starting from 25°C (77°F), 4% power lost with each 10°C (50°F) increment cos phi =0.8

Prime: These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation. 10% overload power can be supplied for one hour in 12.

Standby: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of the utility power failure. No overload is permitted.

\* Other voltages are available: 415/240, 380/220, 220/127, 440/254, 208/120.

DIMENSIONS

		Open	Canopy
Length	mm (in)	4200 (165.3)	4500 (177.1)
Width	mm (in)	1460 (57.4)	1800 (70.8)
Height	mm (in)	2090 (82.2)	2400 (94.4)

WEIGHTS

		Open	Canopy
Shipping volume	m <sup>3</sup> (ft <sup>3</sup> )	12.51 (440.39)	19.44 (685.35)
Dry weight	kg (lb)	3565 (7859)	5490 (12103)

All weights and dimensions are subject to variation, dependent upon customer specification.

SOUND POWER LEVEL

		Canopy
Sound power level of generator	Lwa	101



## JCB GENERATORS | G600QX / G600X

### ENGINE

		50Hz	60Hz
Rated output	kW	523	
Make		Scania	
Model		DC16 44A (10-27)	
Injection type		Direct	
Aspiration		Turbo Aftercooled	
Number of cylinders		8 - V	
Bore and Stroke	mm	127x154	
Displacement	l	15.6	
Cooling		Water	
Lube oil specification		ACEA E3, E4 or E5	
Oil consumption	l/h	<0.3%	
Compression		16:01	18:01
Maximum oil capacity	l	35	
Minimum oil capacity	l	30	
Governing		Electronic	
Engine speed	rpm	1500	1800

### STARTING SYSTEM

Starter motor output	kW	6.7
Starter motor output	CV	8.98
Battery capacity	Ah	2x50
Voltage	vDC	24

### AIR REQUIREMENT

		50Hz	60Hz
Air requirement for combustion @ 100% load	m <sup>3</sup> /h	2368.1	2368.1
Air requirement for combustion @ 100% load	kg/min	37	44

### ALTERNATOR

Make	Newage-Stamford	
Model	HCI 544	
Insulation	Class H	
Pole	4	
AVR	AS440	

### FUEL TANK CAPACITY

Open generator	l (gal)	740 (162.8)
Canopy generator	l (gal)	740 (162.8)

### FUEL CONSUMPTION @ 100% LOAD

		50Hz	60Hz
Prime	l/hr	109.62	109.62
Standby	l/hr	119.2	119.88

### EXHAUST SYSTEM

		50Hz	60Hz
Maximum exhaust temperature	°C	524	478
Maximum exhaust temperature	°F	975.2	893
Exhaust gas flow	kg/h	2340	2760
Heat rejection	Kcal/Kwh	496.8	569.2
Maximum back pressure	kPa (mbar)	9.81 (98.1)	9.81 (98.1)



JCB Power Products Limited, Rocester, Staffordshire ST14 5JP. Tel: +44 (0)1889 590312. www.jcb.com

JCB reserves the right to change specifications without notice. Illustrations shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.



9999/5437 06/09 Issue 1